# **Feature-LIGHTZ**





SLDL614T White




SLDL614T Black





## **Feature - LIGHTZ**

- create a striking focal point to draw attention to design & decor
- 2.2W
- dimmable
- use indoors for reading / features
- constant current (Max 700mA)



#### **Options**

#### Beam angle



30°

CCT





CRI

Professional series (P) CRI 90

#### Trim colour



White

#### Power supply - constant current

Ordered separately

#### 230V circuit (@700mA) only 2700K, 3000K, 4000K

1-3 lights TE dimmable SE-9-350-700 TE dimmable SE-15-350-700 3-6 lights

3-13 lights dimmable SE-40-300-1050\* (5-19 R, 3-12 G)

Contact Switch Lighting for Casambi Smart Control options.

#### 12 or 24VDC circuit - only 2700K, 3000K, 4000K

LDD-700LW power supply @ 12VDC 1-3 lights 1-6 lights LDD-700LW power supply @ 24VDC



Scan to view driver options

#### **Product information**

Example: 3000K

Contact Switch Lighting for data of other variants

Luminaire	Forward	Delivered	Insul	sulation coverable	
power (W)	voltage (V <sub>f</sub> )	lumens (lm)	NZ	AU UK/EU	
2.2	3.2	175	IC-F	IC-4	










Cut-out Ø43mm

Hole depth >30mm

### how to specify Feature-LIGHTZ

Please confirm model option availability from our website. Note: driver is ordered separately.

e.g. code = SLDL614T-30-30-P-W



Please see www.switch-lighting.co.nz for specifications, lux levels, SDoCs, ies files and installation instructions.

















