

Feature-LIGHTZ



SLDL614T
White




SLDL614T
Black



Feature-LIGHTZ

- + create a striking focal point to draw attention to design & decor
- + 2.2W
- + dimmable
- + use indoors for reading / features
- + IP44
- + constant current (Max 700mA)



Options

Beam angle



30°

CCT



2700K



3000K



4000K

CRI

Professional series (P) CRI 90

Trim colour



White



Black

Power supply – constant current

Ordered separately

230V circuit (@700mA) only 2700K, 3000K, 4000K

- 1-3 lights TE dimmable SE-9-350-700
- 3-6 lights TE dimmable SE-15-350-700
- 3-13 lights dimmable SE-40-300-1050* (5-19 R, 3-12 G)

Contact Switch Lighting for Casambi Smart Control options.

12 or 24VDC circuit – only 2700K, 3000K, 4000K

- 1-3 lights LDD-700LW power supply @ 12VDC
- 1-6 lights LDD-700LW power supply @ 24VDC



Scan to view driver options

Product information

Example: 3000K

Contact Switch Lighting for data of other variants

Luminaire power (W)	Forward voltage (V _f)	Delivered lumens (lm)	Insulation coverable		
			NZ	AU	UK/EU
2.2	3.2	175	IC-F	IC-4	✓



Size 50x19mm



Cut-out Ø43mm



Hole depth >30mm



IP44

how to specify Feature-LIGHTZ

Please confirm model option availability from our website. **Note: driver is ordered separately.**

e.g. code = **S**LDL614T-**30**-**30**-**P**-**W**

Model	Beam	CCT	CRI	Trim Colour	Market
S LDL614T	30 = 30°	27 = 2700K 30 = 3000K 40 = 4000K	P = 90	W = White B = Black	1 = NZ 1 = Aust 2 = UK 3 = EU

Please see www.switch-lighting.co.nz for specifications, lux levels, SDoCs, ies files and installation instructions.



Warranty
7yr Luminaire
5yr Driver

L70 (30,000 h)

