M-LIGHTZ





SL900 Constant Current
SL910 Constant Voltage



Natural Anodised Aluminium



Black Anodised Aluminium




White Aluminium



Matt Bronze Anodised Aluminium



316 Stainless Steel



Copper




Matt Black Anodised Aluminium

SWITCH Lighting®

M-LIGHTZ

- a superb luminaire for creating captivating accent lighting
- use outdoors under soffits
- use indoors for feature lighting
- IP67
- constant current (350 & 500mA) / constant voltage (12 or 24VDC)



Options

Beam angle



22° 38° 45°

CCT



2700K 3000K 4000K

CRI

Professional series (P) CRI 90

Trim colour



Natural Anodised Aluminium | Black Anodised Aluminium | White Aluminium | 316 Stainless Steel | Copper | Matt Black Anodised Aluminium | Matt Bronze Anodised Aluminium

230VAC power supply included

SL900 M-LIGHTZ – **constant current**
White | Natural | Black - Max 500mA dimmable.
SS | Copper - Max 350mA non-dimming*.
*Optional dimming driver ordered separately

Contact Switch Lighting for Casambi Smart Control options.

12 or 24VDC power supply

Ordered separately
SL910 M-LIGHTZ – **constant voltage**
requires a power supply with 12 or 24VDC output.
Q4-12V-20W (IP20) 1-3 lights in parallel
SLDV-12V-40W (IP67) 1-6 lights in parallel
Please refer online for cable size requirements (voltage drop)

Product information

Table is based on: **3000K**
Contact Switch Lighting for data of other variants

Model	System power (W)	Luminaire power (W)	Forward voltage (V_f)	Delivered lumens (lm)	Insulation coverable NZ	AU	UK/EU
SL900 white/natural/black	6.25	5	9.5	400	IC-F	IC-4	√
SL900 SS/copper	4.4	3.5	9.5	290	IC-F	IC-4	√
SL910 white/natural/black	N/A	4.2	11-30	320	IC-F	IC-4	√
SL910 SS/copper	N/A	3.6	11-30	270	IC-F	IC-4	√



Size 54X33mm | Cut-out Ø44-46mm | Hole depth >40mm



SL900 Front | SL910 Front & rear

How to specify M-LIGHTZ

Please confirm model option availability from our website. **Note: SL910 power supply is ordered separately.**

e.g. code = SL900-45-30-P-N

Model	Beam	CCT	CRI	Trim Colour	Market
SL900 SL910	22 = 22° 38 = 38° 45 = 45°	27 = 2700K 30 = 3000K 40 = 4000K	P = 90	N = Natural Anodised Aluminium B = Black Anodised Aluminium W = White Aluminium SS = 316 Stainless Steel C = Copper MB = Matt Black Anodised Aluminium MZ = Matt Bronze Anodised Aluminium	= NZ 1 = Aust 2 = UK 3 = EU

Please see **www.switch-lighting.co.nz** for specifications, lux levels, SDoCs, ies files and installation instructions.

