

# PILLAR Light 2



Corner cut  
SLBL120F Constant Voltage  
SLBL122F Constant Current




Straight cut  
SLBL121F Constant Voltage  
SLBL123F Constant Current





# PILLAR Light 2

- + enhance the aesthetic appeal of outdoor spaces
- + use for gardens / paths / driveways
- + solid untreated hardwood
- + easy installation
- + low maintenance
- + IP67
- + constant current (Max 500mA) /constant voltage (12 or 24VDC)



## Options

### Beam angle



wide

### CCT



2700K



3000K



4000K  
CV only

### CRI

CRI 90 (2700K/3000K/4000K)

### Trim colour



Copper

### Use with

LED protector to protect from power and wiring hazards  
Waterproof cable connectors

### 230VAC power supply – constant current

Ordered separately

Max 500mA

See Tips & Tricks on our website for driver options.

### 12 or 24VDC power supply – constant voltage

Ordered separately

Q4-12V-20W (IP20) 1-3 lights in parallel

SLDV-12V-40W (IP67) 1-6 lights in parallel

Please refer online for cable size requirements (voltage drop)



Scan to view driver options

## Product information

Table is based on: 3000K

Contact Switch Lighting for data of other variants

Model	Luminaire power (W)	Forward voltage (V <sub>f</sub> )	Delivered lumens (lm)
SLBL122F   SLBL123F constant current (CC)	3	6	310
SLBL120F   SLBL121F constant voltage (CV)	4.2	11-30	320



Size  
1100x95x95mm

## How to specify PILLAR Light 2

Please confirm model option availability from our website. **Note: driver is ordered separately.**

e.g. code = **SLBL120F-W127-C**

Model	Beam	CCT	Trim Colour	Market
SLBL120F = corner cut constant voltage SLBL121F = straight cut constant voltage SLBL122F = corner cut constant current SLBL123F = straight cut constant current	W1 = wide angle	27 = 2700K 30 = 3000K 40 = 4000K (CV only)	C = Copper	■ = NZ 1 = Aust 2 = UK 3 = EU

This product is made from natural timber. As such it may have tight knots or other slight imperfections.

Our copper variant is true copper and may contain small natural flaws. Over time, it will develop a patina, darkening in colour to a variety of rich tones. This process will be slower in areas where the fitting is not exposed to moisture.

Please see [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specifications, lux levels, SDoCs, ies files and installation instructions.



Warranty  
5 Years

L70 (60,000 h)

PURE COLOUR  
HIGH CRI DOWNLIGHTS

CONSTANT  
CURRENT

CONSTANT  
VOLTAGE

