

Installation Instructions – PM167

SL900 / SL901 M-LIGHTZ

Classification: IC-F / IC-4

Recessed luminaire where approved fixed building insulation material that can be safely be continuously exposed to 90°C is allowed to abut and cover the luminaire.

Constant current:

350mA (max) stainless steel, copper
500mA (max) natural or black anodise, white

Approved insulation:

Pink Batts, Bradford Gold, InsulPro Polyester insulation, Ecofleece, Autex Greenstuf, Earthwool, Premier insulation.

Contact Switch Lighting for other insulation information.

Caution:

Always turn power off when connecting or disconnecting luminaires.

Note:

IP67 front face only.

White models suitable for indoor use only.

Warranty:

Luminaire: 7 years (5 years if outdoors)

Driver: 5 years

Proof of purchase is required. See website for full warranty conditions.

How many constant current lights per driver?

Click on the QR code to check max & min number of lights to connect plus dimmer information or visit

www.switch-lighting.co.nz/

Library / Tips and Tricks




Required clearance: Standard

Required clearance from structural members and building elements:

SCB = 0mm HCB = 0mm

Cut-out



Installation:

(by registered electrician only)

If using non-standard driver, connect lights in **SERIES**.

Standard driver supplied with light uses 1 driver per light.

