



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 56.24 lm/W
MODEL		I _{max} (cd)	648.9	S/MH (C0/180)		0.70
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)		0.68
RATED VOLTAGE (V)		TOTAL FLUX (lm)	365.53	η UP,DN (C0-180)		0.0,49.6
NOMINAL FLUX (lm)	365.531	CIE CLASS	DIRECT	η UP,DN (C180-360)		0.0,50.4
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM		0.75
TEST VOLTAGE (V)		η down (%)	100.0	CIBSE SHR MAX		0.75



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	564.5	550.2	546.4	550.6	560.3	551.8	559.8	559.7	0- 10	56.77	56.77	15.5,15.5
20	362.4	349.0	345.6	357.1	366.7	352.6	353.5	357.2	10- 20	127.6	184.3	50.4,50.4
30	182.4	165.1	164.2	170.9	180.3	171.3	176.3	177.5	20- 30	118.4	302.8	82.8,82.8
40	27.68	24.57	23.52	23.25	24.49	24.54	26.61	24.89	30- 40	52.74	355.5	97.3,97.3
50	3.733	3.233	3.366	2.951	3.585	3.290	3.531	3.255	40- 50	7.942	363.5	99.4,99.4
60	0.9572	0.6932	0.8201	0.6155	0.8583	0.7405	0.9230	0.6777	50- 60	1.445	364.9	99.8,99.8
70	0.2823	0.2089	0.2338	0.1977	0.2506	0.2302	0.2969	0.2117	60- 70	0.4218	365.3	99.9,99.9
80	0.1024	0.0880	0.0869	0.0899	0.0928	0.0946	0.1169	0.0928	70- 80	0.1576	365.5	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.0504	365.5	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	545	415
80	469	398
75	512	424
70	657	544
65	938	803
60	1523	1306
55	2324	2257
50	4620	4169
45	10742	10248


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 24 July 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm																	
NAME: SLDL216T-4030P-TWD09									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.: Switch Lighting									SUR.:						Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.163	.093	.029	.157	.089	.028	.144	.083	.026	.132	.076	.025	.122	.071	.023	
2.0	.155	.085	.026	.149	.082	.025	.139	.077	.024	.129	.072	.023	.120	.068	.021	
3.0	.147	.078	.023	.142	.076	.023	.133	.072	.022	.125	.069	.021	.118	.065	.020	
4.0	.140	.073	.021	.136	.071	.021	.128	.068	.020	.121	.065	.020	.114	.062	.019	
5.0	.133	.068	.020	.130	.066	.019	.123	.064	.019	.117	.062	.018	.111	.059	.018	
6.0	.127	.064	.018	.124	.063	.018	.118	.061	.018	.113	.059	.017	.108	.057	.017	
7.0	.121	.060	.017	.119	.059	.017	.114	.057	.017	.109	.056	.016	.104	.054	.016	
8.0	.116	.057	.016	.114	.056	.016	.110	.055	.016	.105	.053	.015	.101	.052	.015	
9.0	.112	.054	.015	.110	.053	.015	.106	.052	.015	.102	.051	.015	.098	.050	.014	
10.0	.107	.051	.014	.105	.051	.014	.102	.050	.014	.098	.049	.014	.095	.048	.014	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.146	.135	.126	.100	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.154	.133	.115	.132	.114	.099	.090	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.141	.113	.092	.121	.098	.080	.083	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.130	.099	.075	.111	.085	.065	.077	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.121	.087	.062	.104	.075	.054	.071	.052	.038	.041	.031	.022	.013	.010	.007	
6.0	.113	.077	.052	.097	.067	.045	.067	.047	.032	.039	.028	.019	.013	.009	.006	
7.0	.106	.069	.044	.091	.060	.038	.063	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.100	.063	.038	.086	.055	.033	.060	.038	.023	.035	.023	.014	.011	.007	.005	
9.0	.095	.058	.033	.082	.050	.028	.057	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.091	.053	.029	.078	.046	.025	.054	.033	.018	.032	.019	.011	.010	.006	.003	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm											
NAME: SLDL216T-4030P-TWD09					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: Switch Lighting					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	20.9	21.7	21.1	21.9	22.0	20.6	21.4	20.8	21.6	21.7
	3H	20.7	21.5	21.0	21.7	21.9	20.4	21.2	20.7	21.4	21.6
	4H	20.6	21.4	20.9	21.6	21.8	20.3	21.1	20.6	21.3	21.5
	6H	20.5	21.2	20.8	21.5	21.7	20.2	20.9	20.5	21.2	21.4
	8H	20.5	21.2	20.8	21.4	21.7	20.2	20.9	20.5	21.1	21.4
	12H	20.5	21.1	20.8	21.4	21.6	20.2	20.8	20.5	21.1	21.3
4H	2H	20.6	21.4	20.9	21.6	21.8	20.3	21.1	20.6	21.3	21.5
	3H	20.5	21.1	20.8	21.4	21.6	20.2	20.8	20.5	21.1	21.3
	4H	20.4	20.9	20.7	21.2	21.5	20.1	20.6	20.4	20.9	21.2
	6H	20.3	20.8	20.6	21.1	21.4	20.0	20.5	20.3	20.8	21.2
	8H	20.2	20.7	20.6	21.0	21.4	19.9	20.4	20.3	20.7	21.1
	12H	20.2	20.6	20.6	21.0	21.4	19.9	20.3	20.3	20.7	21.1
8H	4H	20.2	20.7	20.6	21.0	21.4	19.9	20.4	20.3	20.7	21.1
	6H	20.1	20.5	20.5	20.9	21.3	19.8	20.2	20.2	20.6	21.0
	8H	20.1	20.4	20.5	20.8	21.3	19.8	20.1	20.2	20.5	21.0
	12H	20.0	20.3	20.5	20.7	21.2	19.7	20.0	20.2	20.4	20.9
12H	4H	20.2	20.6	20.6	21.0	21.4	19.9	20.3	20.3	20.7	21.1
	6H	20.1	20.4	20.5	20.8	21.3	19.8	20.1	20.2	20.5	21.0
	8H	20.0	20.3	20.5	20.7	21.2	19.7	20.0	20.2	20.4	20.9
Variations with the observer position at spacings:											
S = 1.0H	+ 4.8 / -13.5					+ 4.2 / -12.9					
1.5H	+ 7.3 / -12.2					+ 6.6 / -11.0					
2.0H	+ 6.8 / - 7.6					+ 6.7 / - 7.2					

CIE Pub.117, 365.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.5)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	90	84	80	89	84	80	89	83	80	77
0.80	97	92	88	96	91	88	95	91	88	84
1.00	101	96	92	100	95	92	99	95	92	88
1.25	105	100	97	104	99	96	102	98	95	92
1.50	107	103	100	106	102	99	104	101	98	94
2.00	109	106	103	108	105	102	105	103	100	95
2.50	111	107	105	109	106	104	106	104	102	96
3.00	112	109	107	111	108	106	107	105	103	97
4.00	114	112	110	112	110	108	109	107	106	99
5.00	116	113	112	113	112	110	109	108	107	100
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

AAI Figure

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:229.90V I:0.0300A P:6.5000W PF:0.9570 Freq:50.00Hz Lamp Flux:365.53lx1 lm		
NAME: SLDL216T-4030P-TWD09	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	884
L_0~180 (75) av	486
L_0~180 (85) av	501
L_90~270 (65) av	888
L_90~270 (75) av	492
L_90~270 (85) av	530
L_45 (65) av	656
L_45 (75) av	407
L_45 (85) av	487

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:24 July 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 24 July 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

```