



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 42.95 lm/W
MODEL		I _{max} (cd)	1023	S/MH (C0/180)		0.58
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)		0.62
RATED VOLTAGE (V)		TOTAL FLUX (lm)	399.43	η UP,DN (C0-180)		0.0,44.5
NOMINAL FLUX (lm)	399.434	CIE CLASS	DIRECT	η UP,DN (C180-360)		0.0,55.5
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM		0.50
TEST VOLTAGE (V)		η down (%)	100.0	CIBSE SHR MAX		0.55



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	743.0	684.1	670.6	719.7	817.7	855.2	873.5	827.3	0- 10	83.47	83.47	20.9,20.9
20	356.3	325.4	324.1	364.1	412.3	461.3	480.2	429.4	10- 20	159.7	243.1	60.9,60.9
30	130.3	119.9	123.2	137.8	158.0	158.3	153.5	154.5	20- 30	112.9	356.1	89.1,89.1
40	7.963	8.095	8.222	7.790	9.588	18.30	18.94	11.77	30- 40	38.57	394.6	98.8,98.8
50	2.041	2.084	2.054	1.742	2.219	2.381	2.062	1.994	40- 50	3.463	398.1	99.7,99.7
60	0.4724	0.4887	0.5061	0.4417	0.5221	0.6182	0.6050	0.5377	50- 60	1.013	399.1	99.9,99.9
70	0.0828	0.0827	0.0833	0.0849	0.0774	0.0762	0.0770	0.0729	60- 70	0.2515	399.4	100,100
80	0.0420	0.0391	0.0384	0.0420	0.0383	0.0380	0.0378	0.0326	70- 80	0.0636	399.4	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.0181	399.4	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	180	145
80	193	176
75	199	192
70	193	194
65	404	403
60	753	805
55	1453	1478
50	2531	2540
45	4218	4308


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 03 August 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm																	
NAME: SLDL226T-30SDP-TWD10									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.: Switch Lighting									SUR.:						Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.153	.087	.028	.146	.084	.027	.134	.077	.025	.123	.071	.023	.112	.065	.021	
2.0	.144	.079	.024	.139	.076	.024	.128	.071	.022	.119	.067	.021	.110	.062	.020	
3.0	.136	.072	.022	.131	.070	.021	.123	.066	.020	.115	.063	.019	.107	.059	.018	
4.0	.129	.067	.020	.125	.065	.019	.117	.062	.019	.110	.059	.018	.104	.057	.017	
5.0	.122	.062	.018	.119	.061	.018	.113	.059	.017	.107	.056	.017	.101	.054	.016	
6.0	.117	.058	.017	.114	.057	.017	.108	.055	.016	.103	.053	.016	.098	.052	.015	
7.0	.111	.055	.016	.109	.054	.015	.104	.053	.015	.099	.051	.015	.095	.049	.015	
8.0	.107	.052	.015	.104	.051	.015	.100	.050	.014	.096	.049	.014	.092	.047	.014	
9.0	.102	.050	.014	.100	.049	.014	.096	.048	.014	.093	.047	.013	.089	.045	.013	
10.0	.098	.047	.013	.097	.047	.013	.093	.046	.013	.090	.045	.013	.087	.044	.013	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio									Ceiling Cavity Exitance Coefficients (CCEC)						
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.169	.158	.147	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.153	.133	.116	.131	.114	.100	.090	.079	.070	.052	.046	.041	.017	.015	.013	
3.0	.139	.113	.093	.119	.098	.081	.082	.068	.057	.047	.040	.033	.015	.013	.011	
4.0	.127	.098	.076	.109	.085	.066	.075	.059	.047	.043	.035	.028	.014	.011	.009	
5.0	.118	.086	.063	.101	.075	.055	.070	.052	.039	.040	.031	.023	.013	.010	.008	
6.0	.109	.077	.053	.094	.066	.046	.065	.046	.033	.038	.027	.019	.012	.009	.006	
7.0	.102	.069	.045	.088	.060	.039	.061	.042	.028	.035	.025	.017	.011	.008	.005	
8.0	.096	.062	.039	.083	.054	.034	.057	.038	.024	.033	.022	.014	.011	.007	.005	
9.0	.091	.057	.034	.078	.049	.029	.054	.035	.021	.032	.020	.012	.010	.007	.004	
10.0	.086	.052	.029	.075	.045	.026	.052	.032	.018	.030	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm											
NAME: SLDL226T-30SDP-TWD10					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: Switch Lighting					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		16.2	17.0	16.4	17.1	17.3	15.4	16.2	15.6	16.3	16.5
	3H	16.0	16.7	16.3	16.9	17.1	15.2	16.0	15.5	16.2	16.3
	4H	15.9	16.6	16.2	16.8	17.0	15.2	15.8	15.4	16.1	16.3
	6H	15.9	16.5	16.1	16.7	17.0	15.1	15.7	15.4	16.0	16.2
	8H	15.8	16.4	16.1	16.7	16.9	15.0	15.6	15.3	15.9	16.2
	12H	15.8	16.4	16.1	16.6	16.9	15.0	15.6	15.3	15.8	16.1
4H	2H	15.9	16.6	16.2	16.8	17.0	15.2	15.8	15.4	16.1	16.3
	3H	15.8	16.4	16.1	16.6	16.9	15.0	15.6	15.3	15.8	16.1
	4H	15.7	16.2	16.0	16.5	16.8	14.9	15.4	15.2	15.7	16.0
	6H	15.6	16.1	15.9	16.4	16.7	14.8	15.3	15.2	15.6	15.9
	8H	15.5	16.0	15.9	16.3	16.7	14.7	15.2	15.1	15.5	15.9
	12H	15.5	15.9	15.9	16.2	16.6	14.7	15.1	15.1	15.5	15.9
8H	4H	15.5	16.0	15.9	16.3	16.7	14.7	15.2	15.1	15.5	15.9
	6H	15.4	15.8	15.8	16.2	16.6	14.6	15.0	15.1	15.4	15.8
	8H	15.4	15.7	15.8	16.1	16.5	14.6	14.9	15.0	15.3	15.8
	12H	15.3	15.6	15.8	16.0	16.5	14.5	14.8	15.0	15.2	15.7
12H	4H	15.5	15.9	15.9	16.2	16.6	14.7	15.1	15.1	15.5	15.9
	6H	15.4	15.7	15.8	16.1	16.5	14.6	14.9	15.0	15.3	15.8
	8H	15.3	15.6	15.8	16.0	16.5	14.5	14.8	15.0	15.2	15.7
Variations with the observer position at spacings:											
S = 1.0H		+ 5.2 / -10.4					+ 4.8 / - 9.9				
1.5H		+ 7.5 / - 8.3					+ 6.9 / - 6.7				
2.0H		+ 5.3 / - 6.6					+ 4.8 / - 7.3				

CIE Pub.117, 399.4 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.2)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	91	85	82	90	85	82	90	85	81	78
0.80	98	93	89	97	92	89	96	92	89	85
1.00	102	97	93	101	96	93	99	96	93	89
1.25	105	100	97	104	100	97	102	99	96	92
1.50	108	103	100	106	103	100	104	101	99	95
2.00	110	106	103	108	105	102	106	103	101	96
2.50	111	108	105	110	107	104	107	104	102	97
3.00	113	110	107	111	108	106	108	105	104	98
4.00	115	112	110	112	110	109	109	107	106	99
5.00	116	114	112	114	112	110	110	108	107	100
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.00V I:0.0420A P:9.3000W PF:0.9770 Freq:50.00Hz Lamp Flux:399.434x1 lm		
NAME: SLDL226T-30SDP-TWD10	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	416
L_0~180 (75) av	193
L_0~180 (85) av	162
L_90~270 (65) av	473
L_90~270 (75) av	187
L_90~270 (85) av	159
L_45 (65) av	447
L_45 (75) av	186
L_45 (85) av	153

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 03 August 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

```