



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 54.75 lm/W
MODEL		I _{max} (cd)	1121	S/MH (C0/180)		0.55
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)		0.58
RATED VOLTAGE (V)		TOTAL FLUX (lm)	405.18	η UP,DN (C0-180)		0.0,48.5
NOMINAL FLUX (lm)	405.185	CIE CLASS	DIRECT	η UP,DN (C180-360)		0.0,51.5
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM		0.50
TEST VOLTAGE (V)		η down (%)	100.0	CIBSE SHR MAX		0.60



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	841.4	814.3	790.9	799.8	812.9	843.7	864.9	867.7	0- 10	91.41	91.41	22.6,22.6
20	426.1	392.4	382.1	395.2	400.4	407.0	439.2	448.7	10- 20	173.3	264.7	65.3,65.3
30	76.53	73.88	71.86	72.78	75.17	79.14	80.64	77.97	20- 30	102.6	367.3	90.6,90.6
40	12.87	12.98	13.30	13.01	14.11	13.11	12.48	12.69	30- 40	21.60	388.9	96,96
50	6.588	6.735	6.731	6.719	6.723	6.571	6.552	6.518	40- 50	6.683	395.5	97.6,97.6
60	4.430	4.553	4.523	4.558	4.495	4.445	4.460	4.369	50- 60	4.914	400.5	98.8,98.8
70	2.002	2.061	2.081	2.119	2.077	2.073	2.075	1.984	60- 70	3.182	403.6	99.6,99.6
80	0.5287	0.5261	0.5228	0.5585	0.5290	0.5386	0.5418	0.4981	70- 80	1.351	405.0	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.1989	405.2	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1386	1365
80	2420	2400
75	3891	3974
70	4652	4850
65	5810	5937
60	7041	7212
55	7573	7682
50	8146	8349
45	9195	9443


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 16 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm																	
NAME: SLDL280F-30SDP-BGDD15									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.: Switch Lighting									SUR.:						Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.155	.088	.028	.148	.085	.027	.136	.078	.025	.125	.072	.023	.114	.066	.021	
2.0	.146	.080	.024	.140	.077	.024	.130	.072	.022	.120	.067	.021	.111	.063	.020	
3.0	.137	.073	.022	.132	.071	.021	.123	.067	.020	.115	.063	.019	.108	.060	.018	
4.0	.129	.067	.020	.125	.065	.019	.117	.062	.019	.110	.059	.018	.104	.057	.017	
5.0	.122	.062	.018	.118	.061	.018	.112	.058	.017	.106	.056	.017	.100	.054	.016	
6.0	.116	.058	.017	.113	.057	.016	.107	.055	.016	.102	.053	.016	.097	.051	.015	
7.0	.110	.054	.015	.107	.054	.015	.103	.052	.015	.098	.050	.015	.094	.049	.014	
8.0	.105	.051	.014	.103	.051	.014	.098	.049	.014	.094	.048	.014	.091	.047	.014	
9.0	.100	.049	.014	.098	.048	.013	.095	.047	.013	.091	.046	.013	.088	.045	.013	
10.0	.096	.046	.013	.095	.046	.013	.091	.045	.013	.088	.044	.012	.085	.043	.012	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.158	.147	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.153	.133	.116	.131	.114	.100	.090	.079	.070	.052	.046	.041	.017	.015	.013	
3.0	.139	.113	.093	.119	.098	.081	.082	.068	.057	.047	.040	.033	.015	.013	.011	
4.0	.127	.098	.076	.109	.085	.066	.075	.059	.047	.043	.035	.028	.014	.011	.009	
5.0	.117	.086	.063	.101	.075	.055	.069	.052	.039	.040	.031	.023	.013	.010	.008	
6.0	.109	.077	.053	.094	.066	.046	.065	.046	.033	.038	.027	.020	.012	.009	.006	
7.0	.102	.069	.045	.088	.059	.040	.061	.042	.028	.035	.025	.017	.011	.008	.006	
8.0	.096	.062	.039	.082	.054	.034	.057	.038	.024	.033	.022	.014	.011	.007	.005	
9.0	.090	.057	.034	.078	.049	.030	.054	.035	.021	.031	.020	.013	.010	.007	.004	
10.0	.086	.052	.030	.074	.045	.026	.051	.032	.018	.030	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm											
NAME: SLDL280F-30SDP-BGDD15					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: Switch Lighting					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	16.1	16.9	16.3	17.0	17.2	16.2	17.0	16.5	17.2	17.3
	3H	16.6	17.3	16.8	17.5	17.7	16.7	17.5	17.0	17.7	17.8
	4H	16.7	17.4	17.0	17.6	17.9	16.9	17.6	17.2	17.8	18.0
	6H	16.8	17.4	17.1	17.7	17.9	17.0	17.6	17.2	17.8	18.1
	8H	16.8	17.4	17.1	17.6	17.9	16.9	17.6	17.2	17.8	18.1
	12H	16.7	17.3	17.1	17.6	17.9	16.9	17.5	17.2	17.8	18.0
4H	2H	16.3	17.0	16.6	17.2	17.4	16.4	17.1	16.7	17.3	17.6
	3H	16.9	17.5	17.2	17.8	18.0	17.1	17.7	17.4	17.9	18.2
	4H	17.2	17.7	17.5	18.0	18.3	17.3	17.9	17.7	18.2	18.5
	6H	17.2	17.7	17.6	18.0	18.4	17.4	17.9	17.8	18.2	18.6
	8H	17.2	17.7	17.6	18.0	18.4	17.4	17.8	17.8	18.2	18.6
	12H	17.2	17.6	17.6	18.0	18.3	17.4	17.8	17.8	18.1	18.5
8H	4H	17.2	17.6	17.6	18.0	18.3	17.3	17.8	17.7	18.1	18.5
	6H	17.3	17.6	17.7	18.0	18.4	17.5	17.8	17.9	18.2	18.6
	8H	17.3	17.6	17.7	18.0	18.4	17.4	17.8	17.9	18.2	18.6
	12H	17.2	17.5	17.7	18.0	18.4	17.4	17.7	17.9	18.1	18.6
12H	4H	17.1	17.5	17.5	17.9	18.3	17.3	17.7	17.7	18.1	18.5
	6H	17.2	17.6	17.7	18.0	18.4	17.4	17.7	17.9	18.2	18.6
	8H	17.2	17.5	17.7	18.0	18.4	17.4	17.7	17.9	18.1	18.6
Variations with the observer position at spacings:											
S = 1.0H	+ 1.0 / - 0.9					+ 1.0 / - 0.9					
1.5H	+ 2.0 / - 0.7					+ 1.8 / - 0.7					
2.0H	+ 0.4 / - 0.5					+ 0.4 / - 0.5					

CIE Pub.117, 405.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.1)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	79	89	83	79	88	82	79	76
0.80	96	91	87	96	90	87	94	90	87	83
1.00	100	95	91	99	94	91	98	94	91	87
1.25	104	99	96	103	98	95	101	97	95	91
1.50	107	102	99	105	101	98	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	97
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

AAI Figure

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 16 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:229.90V I:0.0340A P:7.4000W PF:0.9660 Freq:50.00Hz Lamp Flux:405.185x1 lm		
NAME: SLDL280F-30SDP-BGDD15	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	5899
L_0~180 (75) av	3969
L_0~180 (85) av	1375
L_90~270 (65) av	5964
L_90~270 (75) av	3979
L_90~270 (85) av	1404
L_45 (65) av	5948
L_45 (75) av	3950
L_45 (85) av	1377

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:16 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 16 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

```