

sLED
by Switch Lighting



SLCD121F
Ø170mm

Commercial lighting



SLCD151F
Ø235mm

Commercial lighting







Commercial Downlights

Lighting excellence for every space

- + low glare UGR<19
- + switchable CCT (3000/4000/5700K) or single CCT (4000K) options
- + flicker free dimmable driver included
- + L70 50,000 hours
- + IP54 front
- + constant current



Options

Beam angle



60°

Switchable CCT



3000K



4000K



5700K

Single CCT



4000K

Trim colour



White

CRI
CRI 90

Product information

Example: 60°, 4000K, CRI 90

Contact Switch Lighting for data of other variants

Model	Power (W)	Driver (mA)	Delivered lumens (lm)	Insulation Coverable		
				NZ	AU	UK/EU
SLCD121	18	450	1600	ICF	IC4	✓
SLCD151	25	650	2300	ICF	IC4	✓

SLCD121F



Size
170x88mm



Cut-out
Ø140-150mm



Hole depth
>88mm



Front

SLCD151F



Size
235x103mm



Cut-out
Ø200-210mm



Hole depth
>103mm



Front

how to specify SLED Commercial

Please confirm model option availability from our website.

e.g. code = **SLCD121F-6040P-TWD62**

Model	Beam	CCT	Pure Colour	Trim Colour	Market
SLCD121F = Ø170mm SLCD151F = Ø235mm	60 = 60°	S3 = 3000K 4000K 5700K (switchable) 40 = 4000K	P = CRI 90	TW = White	= NZ 1 = Aust 2 = UK 3 = EU

Please see www.switch-lighting.co.nz for specifications, lux levels, SDoCs, ies files and installation instructions.

Warranty
5 Years

