sLED
by **Switch Lighting**

Whangaparaoa private residence

Wide angle lighting

**SL50-30-W**

**SL55-30-W**

**SL56-30-W**

Scan to view website

# Downlight

## Lighting excellence for every space

- wide angle flood lighting
- 80% energy savings
- dimming driver
- IP44 front
- constant current




**SL50**




**SL55**




**SL56**

## Options

**Diffuser**
Opaque

**CCT**
3000K
4000K
SL50 only

**Beam angle**
90°

**CRI**
CRI 80

**Trim colour**
White
Black
SL50 only

9-36VDC input options available
Click the QR code for low voltage driver options

## Product information

Example: 3000K
Contact Switch Lighting for data of other variants

| Model | Power (W) | Delivered lumens (lm) | Insulation coverable NZ | AU | UK/EU |
|---|---|---|---|---|---|
| SL50 | 8.6 | 840 | ICF | IC4 | √ |
| SL55 | 12.8 | 1250 | ICF | IC4 | √ |
| SL56 | 12.8 | 1250 | ICF | IC4 | √ |

**SL50**
Size 103x42mm | Cut-out Ø89-92mm | Hole depth >45mm | IP44 Front

**SL55**
Size 120x42mm | Cut-out Ø98-108mm | Hole depth >45mm | IP44 Front

**SL56**
Size 150x42mm | Cut-out Ø122-135mm | Hole depth >45mm | IP44 Front

## how to specify sLED Downlight

e.g. code = SL50-30-W

| Model | | CCT | | Trim Colour |
|---|---|---|---|---|
| SL50<br>SL55<br>SL56 | – | 30 = 3000K<br>40 = 4000K* | – | W = White<br>B = Black* |

*Option only available in SL50.

Please see **www.switch-lighting.co.nz** for specifications, lux levels, SDoCs, ies files and installation instructions.

Warranty
5 Years

L70 (54,000 h)

IC-F ABUTTED & COVERED
IC-4
CONSTANT CURRENT
RoHS