

# sLED

by Switch Lighting



Wide angle lighting



SL50-30-W



SL55-30-W






SL56-30-W

# Downlight

Lighting excellence for every space

- + wide angle flood lighting
- + 80% energy savings
- + dimming driver
- + IP44 front
- + constant current



## Options

**Diffuser**  
Opaque

**CCT**



**Beam angle**



90°

**CRI**

CRI 80

**Trim colour**



## Product information

**Example:** 3000K

Contact Switch Lighting for data of other variants

Model	Power (W)	Delivered lumens (lm)	Insulation coverable		
			NZ	AU	UK/EU
SL50	8.6	840	ICF	IC4	✓
SL55	12.8	1250	ICF	IC4	✓
SL56	12.8	1250	ICF	IC4	✓

SL50



Size 103x42mm



Cut-out Ø89-92mm



Hole depth >45mm



Front

SL55



Size 120x42mm



Cut-out Ø98-108mm



Hole depth >45mm



Front

SL56



Size 150x42mm



Cut-out Ø122-135mm



Hole depth >45mm



Front

## how to specify sLED Downlight

e.g. code = **SL50-30-W**

Model	CCT	Trim Colour
SL50	30 = 3000K	W = White
SL55	40 = 4000K*	B = Black*
SL56		

\*Option only available in SL50.

Please see [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specifications, lux levels, SDoCs, ies files and installation instructions.



Warranty  
5 Years

L70 (54,000h)

