

# sLED

by Switch Lighting



Wide angle lighting



SL50-30-W



SL55-30-W






SL56-30-W



# sLED Downlight

Lighting excellence for every space

- + wide angle flood lighting
- + 80% energy savings
- + dimming driver
- + IP44 front
- + constant current



## Options

**Diffuser**  
Opaque

**CCT**



3000K



4000K  
SL50 only

**Beam angle**



90°

**CRI**

CRI 80

**Trim colour**



White



Black  
SL50 only

9-36VDC input options available  
Scan the QR code for low voltage driver options



## Product information

**Table is based on: 3000K**

Contact Switch Lighting for data of other variants

| Model | Power (W) | Delivered lumens (lm) | Insulation coverable |     |       |
|-------|-----------|-----------------------|----------------------|-----|-------|
|       |           |                       | NZ                   | AU  | UK/EU |
| SL50  | 8.6       | 840                   | ICF                  | IC4 | ✓     |
| SL55  | 12.8      | 1250                  | ICF                  | IC4 | ✓     |
| SL56  | 12.8      | 1250                  | ICF                  | IC4 | ✓     |

SL50



Size  
103x42mm



Cut-out  
Ø89-92mm



Hole depth  
>45mm



Front

SL55



Size  
120x42mm



Cut-out  
Ø98-108mm



Hole depth  
>45mm



Front

SL56



Size  
150x42mm



Cut-out  
Ø122-135mm



Hole depth  
>45mm



Front

## How to specify sLED Downlight

e.g. code = **SL50-30-W**

| Model | CCT         | Trim Colour |
|-------|-------------|-------------|
| SL50  | 30 = 3000K  | W = White   |
| SL55  | 40 = 4000K* | B = Black*  |
| SL56  |             |             |

\*Option only available in SL50.

Please see [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specifications, lux levels, SDoCs, ies files and installation instructions.



Warranty  
5 Years

L70 (54,000h)

