sLED
by **Switch Lighting**





SLBN112
1200mm
General lighting



SLBN315
1500mm
General lighting

PURE COLOUR
HIGH CRI DOWNLIGHTS

Scan to view website

Batten light

Lighting excellence for every space

- up to 140Lm/W
- fast installation
- multiple cable entry points
- flicker free non-dimming driver included
- selectable power output
- IP20
- constant current



Options

Beam angle

120°

CCT

4000K 5000K 6500K

Trim colour

White

CRI

CRI 82, CRI 90, CRI 95

SLBN112

IP20 IK08

Size
1.2mx66mm

SLBN315

IP20 IK08

Size
1.5mx66mm

Product specification information

Model	Length (mm)	Emergency back-up	CCT (K)	Selectable power	Power (W)	Delivered lumens (lm)	CRI
SLBN112-40-W	1200	-	4000	Yes	40	4300	82
					38	4080	
					35	3760	
					32	3440	
SLBN315-40-P-W	1500	-	4000	Yes	60	8400	90
					56	7800	
					52	7200	
					45	6300	
SLBN315-65-P-W	1500	-	6500	Yes	60	8400	90
					56	7800	
					52	7200	
					45	6300	
SLBN335-40-P-W	1500	Yes	4000	No	60	8100	90
SLBN115-40-P-W	1500	-	4000	Yes	60	5700	95
					56	5320	
					52	4940	
					45	4280	
SLBN115-50-P-W	1500	-	5000	Yes	60	5940	95
					56	5540	
					52	5150	
					45	4460	

Please see **www.switch-lighting.co.nz** for specifications, lux levels, SDoCs, ies files and installation instructions.

Warranty
5 Years

L70 (50,000 h)

CONSTANT CC CURRENT

RoHS