



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 75.26 lm/W
MODEL	SLDL315F-27 SL302D	I _{max} (cd)	297.0	S/MH (C0/180)	1.24	
NOMINAL POWER (W)	10.0	LOR (%)	100.0	S/MH (C90/270)	1.24	
RATED VOLTAGE (V)	230V	TOTAL FLUX (lm)	805.28	η UP,DN (C0-180)	0.0,49.7	
NOMINAL FLUX (lm)	805.285	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,50.3	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE (V)		η down (%)	100.0	CIBSE SHR MAX	1.35	



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Jason
Test Date: 09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity: 65.0%
Test Distance: 3.160m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	290.5	290.4	290.5	291.0	291.1	291.3	290.9	291.2	0- 10	28.04	28.04	3.48,3.48
20	272.5	272.7	272.9	274.0	274.0	274.1	274.0	273.9	10- 20	80.01	108.1	13.4,13.4
30	245.4	245.1	245.5	246.6	247.4	246.9	247.0	246.9	20- 30	120.3	228.4	28.4,28.4
40	209.8	209.3	209.4	211.0	211.1	211.0	211.3	211.0	30- 40	143.4	371.8	46.2,46.2
50	167.3	166.7	166.8	168.2	168.7	168.6	168.6	168.4	40- 50	146.4	518.2	64.4,64.4
60	120.1	119.5	119.4	121.0	121.5	122.3	122.9	121.8	50- 60	129.5	647.7	80.4,80.4
70	71.56	70.66	70.53	71.87	72.44	73.34	73.99	72.60	60- 70	95.60	743.3	92.3,92.3
80	25.73	25.01	24.77	25.99	26.34	26.83	27.24	26.13	70- 80	51.03	794.3	98.6,98.6
90	0.0167	0.0134	0.0131	0.0218	0.0899	0.1073	0.0878	0.0221	80- 90	10.97	805.3	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	20318	18362
80	31035	29857
75	38493	37748
70	43833	43164
65	47554	47007
60	50324	50004
55	52621	52348
50	54516	54304
45	56103	55855


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm																	
NAME: SLDL315F-27 SL302D									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.: Switch Lighting									SUR.:						Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.299	.170	.054	.292	.167	.053	.279	.160	.051	.267	.154	.049	.256	.148	.048	
2.0	.284	.156	.048	.278	.153	.047	.266	.148	.046	.256	.143	.045	.246	.139	.044	
3.0	.264	.141	.042	.259	.139	.042	.249	.135	.041	.239	.131	.040	.230	.128	.039	
4.0	.245	.127	.037	.240	.126	.037	.231	.123	.037	.223	.120	.036	.215	.117	.036	
5.0	.227	.116	.034	.223	.114	.033	.215	.112	.033	.207	.109	.033	.200	.107	.032	
6.0	.211	.106	.030	.207	.105	.030	.200	.102	.030	.193	.100	.030	.187	.098	.029	
7.0	.197	.097	.028	.193	.096	.027	.187	.094	.027	.181	.093	.027	.175	.091	.027	
8.0	.184	.090	.025	.181	.089	.025	.175	.087	.025	.170	.086	.025	.165	.084	.025	
9.0	.172	.083	.023	.170	.083	.023	.165	.081	.023	.160	.080	.023	.155	.079	.023	
10.0	.162	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.147	.074	.021	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.060	.053	.047	.019	.017	.015		
2.0	.171	.132	.099	.147	.114	.086	.101	.079	.060	.058	.046	.035	.019	.015	.011		
3.0	.163	.114	.075	.140	.099	.065	.096	.068	.046	.056	.040	.027	.018	.013	.009		
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007		
5.0	.148	.090	.048	.127	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006		
6.0	.141	.082	.040	.121	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005		
7.0	.135	.075	.034	.116	.065	.029	.080	.046	.021	.046	.027	.012	.015	.009	.004		
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004		
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003		
10.0	.117	.060	.023	.100	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm											
NAME: SLDL315F-27 SL302D					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: Switch Lighting					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	27.3	28.8	27.6	29.0	29.2	27.3	28.8	27.6	29.0	29.2
	3H	28.7	30.1	29.0	30.3	30.5	28.7	30.1	29.0	30.3	30.5
	4H	29.2	30.5	29.5	30.8	31.0	29.2	30.5	29.5	30.8	31.0
	6H	29.5	30.7	29.8	31.0	31.3	29.5	30.7	29.8	31.0	31.3
	8H	29.6	30.8	29.9	31.0	31.3	29.5	30.7	29.9	31.0	31.3
	12H	29.6	30.7	29.9	31.0	31.3	29.5	30.7	29.9	31.0	31.3
4H	2H	27.9	29.2	28.2	29.4	29.7	27.9	29.2	28.2	29.5	29.7
	3H	29.4	30.6	29.8	30.9	31.2	29.4	30.6	29.8	30.9	31.2
	4H	30.0	31.1	30.4	31.4	31.7	30.1	31.1	30.4	31.4	31.8
	6H	30.4	31.4	30.8	31.7	32.1	30.4	31.4	30.8	31.7	32.1
	8H	30.6	31.4	31.0	31.8	32.2	30.5	31.4	31.0	31.8	32.2
	12H	30.6	31.4	31.0	31.8	32.2	30.6	31.4	31.0	31.8	32.2
8H	4H	30.2	31.1	30.7	31.5	31.9	30.3	31.1	30.7	31.5	31.9
	6H	30.8	31.5	31.2	31.9	32.3	30.8	31.5	31.2	31.9	32.3
	8H	30.9	31.6	31.4	32.0	32.4	30.9	31.6	31.4	32.0	32.4
	12H	31.0	31.5	31.5	32.0	32.5	31.0	31.5	31.5	32.0	32.5
12H	4H	30.2	31.0	30.7	31.4	31.8	30.3	31.0	30.7	31.4	31.8
	6H	30.8	31.4	31.2	31.9	32.3	30.8	31.4	31.3	31.9	32.3
	8H	31.0	31.5	31.4	32.0	32.4	31.0	31.5	31.4	32.0	32.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 805.3 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.8)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	58	47	40	56	46	40	33
0.80	68	57	50	67	57	50	66	56	49	42
1.00	77	66	59	76	65	59	73	67	58	51
1.25	84	74	67	83	73	66	80	72	65	58
1.50	89	79	72	87	78	72	84	77	71	63
2.00	96	87	81	94	86	80	90	84	79	71
2.50	100	92	86	97	91	85	94	88	83	75
3.00	103	96	91	101	95	90	97	92	88	79
4.00	107	101	97	104	99	95	100	96	93	84
5.00	109	104	101	107	102	99	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity:65.0%
 Test Distance:3.160m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity:65.0%
 Test Distance:3.160m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:230.00V I:0.0480A P:10.700W PF:0.9760 Freq:50.00Hz Lamp Flux:805.285x1 lm		
NAME: SLDL315F-27 SL302D	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	47800
L_0~180 (75) av	38849
L_0~180 (85) av	20731
L_90~270 (65) av	47920
L_90~270 (75) av	38949
L_90~270 (85) av	20510
L_45 (65) av	47871
L_45 (75) av	38893
L_45 (85) av	20552

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:09 September 2019

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 09 September 2019

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

```