



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 85.26 lm/W
MODEL		I _{max} (cd)	383.0	S/MH (C0/180)	1.24	
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)	1.25	
RATED VOLTAGE (V)		TOTAL FLUX (lm)	1057.2	η UP,DN (C0-180)	0.0,49.6	
NOMINAL FLUX (lm)	1057.16	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,50.4	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE (V)		η down (%)	100.0	CIBSE SHR MAX	1.35	



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	375.2	375.1	375.3	375.9	375.9	376.5	376.6	376.2	0- 10	36.20	36.20	3.42,3.42
20	353.1	352.9	353.3	354.6	354.6	355.7	355.8	355.3	10- 20	103.5	139.7	13.2,13.2
30	318.7	317.8	318.5	320.1	319.9	321.2	322.0	321.0	20- 30	156.0	295.8	28,28
40	273.0	271.9	272.7	274.6	274.7	276.1	277.2	275.9	30- 40	186.7	482.4	45.6,45.6
50	218.9	217.2	218.0	220.0	220.6	222.1	223.5	221.9	40- 50	191.5	674.0	63.8,63.8
60	159.7	157.3	157.1	159.7	159.9	161.8	163.5	161.3	50- 60	170.4	844.4	79.9,79.9
70	96.66	94.15	93.39	95.89	96.26	98.93	100.9	98.15	60- 70	127.2	971.6	91.9,91.9
80	36.84	35.09	34.24	36.18	36.29	38.26	39.38	37.16	70- 80	69.61	1041	98.5,98.5
90	0.0246	0.0203	0.0218	0.0857	0.1788	0.1711	0.1350	0.0298	80- 90	15.93	1057	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_v1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	22195	19015
80	31307	29015
75	37434	35663
70	41709	40176
65	44759	43633
60	47146	46223
55	48896	48239
50	50261	49890
45	51541	51253


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm																	
NAME: SLED415F-W1S1P-TWD12 2K7									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.: Switch Lighting									SUR.:						Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.303	.172	.055	.296	.169	.054	.282	.162	.052	.270	.156	.050	.259	.150	.048	
2.0	.287	.157	.048	.281	.155	.048	.269	.150	.046	.258	.145	.045	.248	.140	.044	
3.0	.266	.142	.042	.261	.140	.042	.251	.136	.041	.241	.132	.041	.232	.129	.040	
4.0	.246	.128	.038	.242	.126	.037	.232	.123	.037	.224	.120	.036	.216	.117	.036	
5.0	.228	.116	.034	.224	.115	.033	.216	.112	.033	.208	.110	.033	.201	.107	.032	
6.0	.212	.106	.030	.208	.105	.030	.201	.103	.030	.194	.101	.030	.188	.099	.029	
7.0	.197	.098	.028	.194	.097	.028	.188	.095	.027	.181	.093	.027	.176	.091	.027	
8.0	.184	.090	.025	.181	.089	.025	.176	.088	.025	.170	.086	.025	.165	.085	.025	
9.0	.173	.084	.023	.170	.083	.023	.165	.082	.023	.160	.080	.023	.156	.079	.023	
10.0	.163	.078	.022	.160	.077	.022	.156	.076	.021	.151	.075	.021	.147	.074	.021	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015		
2.0	.172	.132	.099	.147	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011		
3.0	.164	.114	.075	.140	.099	.065	.096	.068	.045	.056	.040	.027	.018	.013	.009		
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007		
5.0	.149	.090	.047	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006		
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005		
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004		
8.0	.128	.069	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.004		
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003		
10.0	.117	.060	.023	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm											
NAME: SLED415F-W1S1P-TWD12 2K7					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: Switch Lighting					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	26.1	27.6	26.4	27.8	28.0	26.1	27.6	26.4	27.8	28.0
	3H	27.5	28.9	27.8	29.2	29.4	27.5	28.9	27.8	29.1	29.4
	4H	28.1	29.4	28.4	29.7	29.9	28.0	29.3	28.3	29.6	29.8
	6H	28.4	29.7	28.8	29.9	30.2	28.3	29.6	28.7	29.8	30.1
	8H	28.5	29.7	28.9	30.0	30.3	28.4	29.6	28.7	29.9	30.2
	12H	28.5	29.7	28.9	30.0	30.3	28.4	29.6	28.8	29.9	30.2
4H	2H	26.7	28.0	27.0	28.3	28.5	26.7	28.0	27.0	28.2	28.5
	3H	28.3	29.4	28.6	29.7	30.0	28.3	29.4	28.6	29.7	30.0
	4H	28.9	30.0	29.3	30.3	30.6	28.9	29.9	29.3	30.3	30.6
	6H	29.4	30.3	29.8	30.7	31.0	29.3	30.3	29.7	30.6	31.0
	8H	29.5	30.4	29.9	30.7	31.1	29.4	30.3	29.8	30.7	31.1
	12H	29.6	30.4	30.0	30.8	31.2	29.5	30.3	29.9	30.7	31.1
8H	4H	29.1	30.0	29.6	30.4	30.8	29.1	30.0	29.5	30.4	30.7
	6H	29.7	30.4	30.2	30.8	31.3	29.7	30.4	30.1	30.8	31.2
	8H	29.9	30.5	30.4	31.0	31.4	29.9	30.5	30.3	30.9	31.4
	12H	30.0	30.6	30.5	31.0	31.5	30.0	30.5	30.4	31.0	31.4
12H	4H	29.1	29.9	29.6	30.3	30.7	29.1	29.9	29.5	30.3	30.7
	6H	29.7	30.4	30.2	30.8	31.3	29.7	30.3	30.2	30.8	31.2
	8H	30.0	30.5	30.4	31.0	31.4	29.9	30.5	30.4	30.9	31.4
Variations with the observer position at spacings:											
S = 1.0H		+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 1057 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.2)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	57	46	40	56	46	39	33
0.80	68	57	49	67	56	49	65	55	49	42
1.00	77	66	58	75	65	58	73	66	58	51
1.25	84	73	66	82	73	66	80	71	65	58
1.50	89	79	72	87	78	72	84	76	70	63
2.00	95	87	81	94	86	80	90	84	78	71
2.50	99	92	86	97	90	85	93	88	83	75
3.00	103	96	90	100	94	89	96	91	87	79
4.00	107	101	96	104	99	95	100	96	92	84
5.00	109	104	100	107	102	99	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_v1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

AAI Figure

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity:65.0%
 Test Distance:3.160m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Jason
 Test Date:08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity:65.0%
 Test Distance:3.160m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:230.00V I:0.0550A P:12.400W PF:0.9820 Freq:50.00Hz Lamp Flux:1057.16x1 lm		
NAME: SLED415F-W1S1P-TWD12 2K7	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Switch Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	44655
L_0~180 (75) av	37228
L_0~180 (85) av	21772
L_90~270 (65) av	44987
L_90~270 (75) av	37524
L_90~270 (85) av	21776
L_45 (65) av	44846
L_45 (75) av	37382
L_45 (85) av	21689

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Jason
Test Date:08 September 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Jason
 Test Date: 08 September 2020

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-i300_V1 SYSTEM V2.0.401
 Humidity: 65.0%
 Test Distance: 3.160m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-i300_V1 SYSTEM V2.0.401
Humidity:65.0%
Test Distance:3.160m [K=1.0000]
Remarks:

```