

# Waterproof connectors

## Fully sealed Waterproof Connector and Junction Boxes.

- + 24A 450VAC, T60 high temperature resistance;
- + 2-6 holders, with terminal (screw type) and connector (plug wire type)
- + IP68 waterproof
- + 0.5-2.5mm<sup>2</sup> wire diameter, 5-9mm / 9-12mm cable diameter

### Connector



### SLAM684-A

Colour	Black
Voltage	16A 450VAC
Housing material	Nylon PA66
Fire-retardant level	V2
Working temperature	T60
Core insert	2 pin / 3 pin / 4 pin
Cross section	0.5 ~ 2.5mm <sup>2</sup>
Cable diameter	5 - 9 mm
IP Code	IP68
Certificates	CE RoHS

### 3-way junction box



### SLAM686-Y

Colour	Black
Voltage	24A 450VAC
Housing material	PC, 94V-2 fire-retardant
Working temperature	T100
Cable diameter	4-8mm / 8-12mm / 10-14mm
IP Code	IP68
Certificates	TUV CE RoHS

### 4-way junction box



### SLAM686-H

Colour	Black
Voltage	24A 450VAC
Housing material	PC, 94V-2 fire-retardant
Working temperature	T100
Cable diameter	4-8mm / 8-12mm / 10-14mm
IP Code	IP68
Certificates	TUV CE RoHS

Warranty  
5 Years