



ZELA look-up table

CCT	Driver Power*	CRI	SLDL214T				SLDL216T				SLDL211T				SLDL212T				SLDL213T			
			9° Lens		15° Lens		20° Lens		30° Honeycomb		40° Honeycomb		40° Prismatic		55° Prismatic		40° ULG clear		55° ULG clear		90° Opaque	
			Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	
2400K	4.3W / 100mA	ICF	-	-	-	-	90	340	90	250	90	230	90	370	90	360	90	370	90	360	90	290
	6.4W / 150mA	ICF	-	-	-	-	90	480	90	360	90	330	90	530	90	520	90	530	90	520	90	420
	7.7W / 180mA	ICF	-	-	-	-	90	560	90	420	90	390	90	620	90	600	90	620	90	600	90	490
	9.4W / 220mA	ICF	-	-	-	-	90	660	90	490	90	450	90	730	90	700	90	730	90	700	90	570
	11.1W / 260mA	CA135	-	-	-	-	90	750	90	560	90	510	90	820	90	800	90	820	90	800	90	640
2700K	4.3W / 100mA	ICF	97	280	90	290	90	360	90	270	90	250	90	400	90	390	90	400	90	390	90	310
	6.4W / 150mA	ICF	97	390	90	410	90	520	90	380	90	360	90	570	90	550	90	570	90	550	90	450
	7.7W / 180mA	ICF	97	460	90	480	90	600	90	450	90	410	90	660	90	640	90	660	90	640	90	520
	9.4W / 220mA	ICF	-	-	90	560	90	700	90	520	90	480	90	780	90	750	90	780	90	750	90	610
	11.1W / 260mA	CA135	-	-	90	640	90	800	90	590	90	550	90	880	90	850	90	880	90	850	90	690
3000K	4.3W / 100mA	ICF	97	290	90	300	90	380	90	280	90	260	90	420	90	400	90	420	90	400	90	330
	6.4W / 150mA	ICF	97	410	90	430	90	540	90	400	90	370	90	590	90	570	90	590	90	570	90	460
	7.7W / 180mA	ICF	97	470	90	500	90	630	90	470	90	430	90	690	90	670	90	690	90	670	90	540
	9.4W / 220mA	ICF	-	-	90	590	90	730	90	550	90	500	90	810	90	780	90	810	90	780	90	630
	11.1W / 260mA	CA135	-	-	90	660	90	830	90	620	90	570	90	910	90	880	90	910	90	880	90	720
4000K	4.3W / 100mA	ICF	97	300	90	320	90	400	90	300	90	270	90	440	90	420	90	440	90	420	90	340
	6.4W / 150mA	ICF	97	430	90	450	90	560	90	420	90	390	90	620	90	600	90	620	90	600	90	490
	7.7W / 180mA	ICF	97	500	90	520	90	660	90	490	90	450	90	720	90	700	90	720	90	700	90	570
	9.4W / 220mA	ICF	-	-	90	620	90	770	90	570	90	530	90	850	90	820	90	850	90	820	90	660
	11.1W / 260mA	CA135	-	-	90	700	90	870	90	650	90	600	90	960	90	930	90	960	90	930	90	750
Sunset Dimming 3000K-1850K	6.4W / 150mA	ICF	-	-	-	-	-	-	90	300	90	280	90	480	90	450	90	480	90	450	-	-
	7.7W / 180mA	ICF	-	-	-	-	-	-	90	340	90	320	90	550	90	520	90	550	90	520	-	-
	9.4W / 220mA	ICF	-	-	-	-	-	-	90	400	90	380	90	650	90	610	90	650	90	610	-	-
	11.1W / 260mA	CA135	-	-	-	-	-	-	90	460	90	420	90	740	90	690	90	740	90	690	-	-
Tunable White 1800K-4000K	4.6W / 100mA	ICF	-	-	-	-	95	250	95	200	95	190	95	290	95	290	95	290	95	290	-	-
	6.9W / 150mA	ICF	-	-	-	-	95	360	95	280	95	270	95	420	95	420	95	420	95	420	-	-
	8.3W / 180mA	ICF	-	-	-	-	95	410	95	330	95	310	95	490	95	490	95	490	95	490	-	-
	10.1W / 230mA	CA135	-	-	-	-	95	480	95	390	95	370	95	570	95	570	95	570	95	570	-	-
	11.9W / 260mA	CA135	-	-	-	-	95	550	95	440	95	420	95	650	95	650	95	650	95	650	-	-

\*Watts quoted are for 20°-90° beam angles. Please check ies files at [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specific model watts for 9° and 15° beam angles. Please note: Tunable White lumens are for 3000K at CRI 95 (Art series).

Typically used for general lighting.

Contact Switch Lighting for all other output and driver options.

Please visit [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for our Lux calculator.

Colour rendition:

Art series: CRI 97 | TM-30-15 R<sub>F</sub>-95 | TM-30-15 R<sub>g</sub>-101

Professional series: CRI 90 | TM-30-15 R<sub>F</sub>-90 | TM-30-15 R<sub>g</sub>-101

how to specify ZELA Tilt

Please confirm model option availability from our website. Not every combination is compatible.

e.g. code = **SLDL211T-4030P-TWD10**

Model	Beam	CCT	CRI	Trim Colour	Driver	Market
SLDL214T = Lens SLDL216T = Honeycomb SLDL212T = ULG clear <b>SLDL211T</b> = Prismatic SLDL213T = Opaque	09 = 9° 15 = 15° 20 = 20° 30 = 30° <b>40</b> = 40° 55 = 55° 90 = 90°	24 = 2400K 27 = 2700K <b>30</b> = 3000K 40 = 4000K SD = Sunset Dimming S2 = Tunable White	<b>P</b> = 90-94 A = 95-98	<b>TW</b> = Textured white TB = Textured black	<b>Phase cut</b> D08 = 100mA (4.3W) D09 = 150mA (6.4W) D15 = 180mA (7.7W) <b>D10</b> = 220mA (9.4W) D11 = 260mA (11.1W) <b>DALI</b> D02 = 180mA (8.3W) D03 = 230mA (10.1W) D04 = 260mA (11.9W) <b>DALI TW</b> D41 = 150mA (6.9W) D42 = 180mA (8.3W) D43 = 230mA (10.1W) D44 = 260mA (11.9W) <b>Casambi TW</b> D50 = 100mA (4.6W) D51 = 150mA (6.8W) D52 = 180mA (8.2W) D53 = 220mA (10W) D54 = 260mA (11.8W)	<b>1</b> = NZ <b>2</b> = Aust <b>3</b> = EU