



ZELA look-up table

CCT	Driver Power*		SLDL224F						SLDL226F				SLDL221F				SLDL220F				SLDL223F	
			9° Lens		15° Lens		20° Lens		30° Honeycomb		40° Honeycomb		40° Prismatic		55° Prismatic		40° Clear		55° Clear		90° Opaque	
			CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm
2400K	4.3W / 100mA	ICF	-	-	-	-	90	350	90	250	90	240	90	370	90	360	90	370	90	360	90	270
	6.4W / 150mA	ICF	-	-	-	-	90	490	90	350	90	350	90	520	90	520	90	520	90	520	90	390
	7.7W / 180mA	ICF	-	-	-	-	90	570	90	410	90	400	90	610	90	600	90	610	90	600	90	450
	9.4W / 220mA	ICF	-	-	-	-	90	670	90	480	90	470	90	710	90	700	90	710	90	700	90	530
	11.1W / 260mA	CA135	-	-	-	-	90	760	90	550	90	530	90	810	90	800	90	810	90	800	90	600
2700K	4.3W / 100mA	ICF	97	280	90	290	90	370	90	270	90	260	90	390	90	390	90	390	90	390	90	290
	6.4W / 150mA	ICF	97	390	90	410	90	530	90	380	90	370	90	560	90	550	90	560	90	550	90	420
	7.7W / 180mA	ICF	97	460	90	480	90	610	90	440	90	430	90	650	90	640	90	650	90	640	90	480
	9.4W / 220mA	ICF	-	-	90	560	90	720	90	510	90	500	90	760	90	750	90	760	90	750	90	570
	11.1W / 260mA	CA135	-	-	90	640	90	810	90	580	90	570	90	860	90	850	90	860	90	850	90	640
3000K	4.3W / 100mA	ICF	97	290	90	300	90	380	90	280	90	270	90	410	90	400	90	410	90	400	90	300
	6.4W / 150mA	ICF	97	410	90	430	90	550	90	390	90	380	90	580	90	570	90	580	90	570	90	430
	7.7W / 180mA	ICF	97	470	90	500	90	640	90	460	90	450	90	680	90	670	90	680	90	670	90	500
	9.4W / 220mA	ICF	-	-	90	590	90	750	90	540	90	520	90	790	90	780	90	790	90	780	90	590
	11.1W / 260mA	CA135	-	-	90	660	90	840	90	610	90	590	90	900	90	880	90	900	90	880	90	670
4000K	4.3W / 100mA	ICF	97	300	90	320	90	400	90	290	90	280	90	430	90	420	90	430	90	420	90	320
	6.4W / 150mA	ICF	97	430	90	450	90	570	90	410	90	400	90	610	90	600	90	610	90	600	90	460
	7.7W / 180mA	ICF	97	500	90	520	90	670	90	480	90	470	90	710	90	700	90	710	90	700	90	530
	9.4W / 220mA	ICF	-	-	90	620	90	780	90	560	90	550	90	830	90	820	90	830	90	820	90	620
	11.1W / 260mA	CA135	-	-	90	700	90	890	90	640	90	620	90	940	90	930	90	940	90	930	90	700
Sunset Dimming 3000K-1850K	6.4W / 150mA	ICF	-	-	-	-	-	-	90	320	90	280	90	460	90	450	90	460	90	450	-	-
	7.7W / 180mA	ICF	-	-	-	-	-	-	90	370	90	330	90	530	90	520	90	530	90	520	-	-
	9.4W / 220mA	ICF	-	-	-	-	-	-	90	430	90	390	90	630	90	610	90	630	90	610	-	-
	11.1W / 260mA	CA135	-	-	-	-	-	-	90	490	90	440	90	710	90	690	90	710	90	690	-	-
Tunable White 1800K-4000K	4.6W / 100mA	ICF	-	-	-	-	95	250	95	200	95	190	95	290	95	290	95	290	95	290	-	-
	6.9W / 150mA	ICF	-	-	-	-	95	360	95	280	95	270	95	420	95	420	95	420	95	420	-	-
	8.3W / 180mA	ICF	-	-	-	-	95	420	95	330	95	310	95	490	95	490	95	490	95	490	-	-
	10.1W / 230mA	CA135	-	-	-	-	95	490	95	390	95	370	95	570	95	570	95	570	95	570	-	-
	11.9W / 260mA	CA135	-	-	-	-	95	560	95	440	95	420	95	650	95	650	95	650	95	650	-	-

*Watts quoted are for 20°-90° beam angles. Please check ies files at www.switch-lighting.co.nz for specific model watts for 9° and 15° beam angles. Please note: Tunable White lumens are for 3000K at CRI 95 (Art series).

Typically used for general lighting.

Contact Switch Lighting for all other output and driver options. Please visit www.switch-lighting.co.nz for our Lux calculator.

Colour rendition:
 Art series: CRI 97 | TM-30-15 R_f-95 | TM-30-15 R_g-101
 Professional series: CRI 90 | TM-30-15 R_f-90 | TM-30-15 R_g-101

how to specify ZELA Deep Fixed

Please confirm model option availability from our website. **Not every combination is compatible.**

e.g. code = **SLDL221F-4030P-TWD10**

Model	Beam	CCT	CRI	Trim Colour	Driver	Market	
SLDL224F = Lens SLDL226F = Honeycomb SLDL220F = Clear glass SLDL221F = Prismatic SLDL223F = Opaque	09 = 9° 15 = 15° 20 = 20° 30 = 30° 40 = 40° 55 = 55° 90 = 90°	24 = 2400K 27 = 2700K 30 = 3000K 40 = 4000K SD = Sunset Dimming S2 = Tunable White	P = 90-94 A = 95-98	TW = Textured white TB = Textured black	Phase cut D08 = 100mA (4.3W) D09 = 150mA (6.4W) D15 = 180mA (7.7W) D10 = 220mA (9.4W) D11 = 260mA (11.1W) DALI D02 = 180mA (8.3W) D03 = 230mA (10.1W) D04 = 260mA (11.9W)	DALI TW D41 = 150mA (6.9W) D42 = 180mA (8.3W) D43 = 230mA (10.1W) D44 = 260mA (11.9W) Casambi TW D50 = 100mA (4.6W) D51 = 150mA (6.8W) D52 = 180mA (8.2W) D53 = 220mA (10W) D54 = 260mA (11.8W)	NZ 1 = Aust 2 = UK 3 = EU