



ZELA look-up table

CCT	Driver Power*	SLDL214F						SLDL216F				SLDL211F				SLDL212F				SLDL213F			
		9° Lens		15° Lens		20° Lens		30° Honeycomb		40° Honeycomb		40° Prismatic		55° Prismatic		40° ULG clear		55° ULG clear		90° Opaque			
		CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm		
2400K	4.3W / 100mA	ICF	-	-	-	-	90	350	90	260	90	240	90	360	90	350	90	360	90	350	90	290	
	6.4W / 150mA	ICF	-	-	-	-	90	490	90	370	90	340	90	520	90	500	90	520	90	500	90	410	
	7.7W / 180mA	ICF	-	-	-	-	90	570	90	430	90	400	90	600	90	580	90	600	90	580	90	480	
	9.4W / 220mA	CA135	-	-	-	-	90	670	90	500	90	470	90	710	90	680	90	710	90	680	90	560	
2700K	4.3W / 100mA	ICF	97	280	90	280	90	370	90	270	90	260	90	390	90	370	90	390	90	370	90	310	
	6.4W / 150mA	ICF	97	390	90	400	90	520	90	390	90	370	90	550	90	530	90	550	90	530	90	440	
	7.7W / 180mA	ICF	97	460	90	470	90	610	90	450	90	430	90	640	90	620	90	640	90	620	90	510	
	9.4W / 220mA	CA135	-	-	90	550	90	710	90	530	90	500	90	750	90	720	90	750	90	720	90	600	
3000K	4.3W / 100mA	ICF	97	290	90	290	90	380	90	290	90	270	90	400	90	390	90	400	90	390	90	320	
	6.4W / 150mA	ICF	97	410	90	420	90	540	90	410	90	380	90	580	90	550	90	580	90	550	90	460	
	7.7W / 180mA	ICF	97	470	90	480	90	630	90	470	90	440	90	670	90	640	90	670	90	640	90	530	
	9.4W / 220mA	CA135	-	-	90	570	90	740	90	550	90	520	90	780	90	750	90	780	90	750	90	620	
4000K	4.3W / 100mA	ICF	97	300	90	310	90	400	90	300	90	280	90	420	90	410	90	420	90	410	90	340	
	6.4W / 150mA	ICF	97	430	90	440	90	570	90	430	90	400	90	600	90	580	90	600	90	580	90	480	
	7.7W / 180mA	ICF	97	500	90	510	90	660	90	500	90	460	90	700	90	670	90	700	90	670	90	560	
	9.4W / 220mA	CA135	-	-	90	600	90	780	90	580	90	550	90	820	90	790	90	820	90	790	90	650	
Sunset Dimming 3000K-1850K	6.4W / 150mA	ICF	-	-	-	-	-	90	310	90	280	90	450	90	450	90	450	90	450	90	450	-	-
	7.7W / 180mA	ICF	-	-	-	-	-	90	360	90	330	90	530	90	530	90	530	90	530	90	530	-	-
	9.4W / 220mA	CA135	-	-	-	-	-	90	420	90	390	90	620	90	620	90	620	90	620	90	620	-	-
Tunable White 4000K-1800K	4.6W / 100mA	ICF	-	-	-	-	95	250	95	200	95	190	95	290	95	290	95	290	95	290	95	290	
	6.9W / 150mA	ICF	-	-	-	-	95	350	95	280	95	270	95	420	95	420	95	420	95	420	95	420	
	8.3W / 180mA	CA135	-	-	-	-	95	410	95	330	95	310	95	490	95	490	95	490	95	490	95	490	
	10.1W / 230mA	Do not cover	-	-	-	-	95	470	95	390	95	370	95	570	95	570	95	570	95	570	95	570	

\*Watts quoted are for 20°-90° beam angles. Please check ies files at [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specific model watts for 9° and 15° beam angles.

Please note: Tunable White lumens are for 3000K at CRI 95 (Art series).

Typically used for general lighting.

Contact Switch Lighting for all other output and driver options.  
Please visit [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for our Lux calculator.

Colour rendition:

Art series: CRI 97 | TM-30-15 R<sub>f</sub>-95 | TM-30-15 R<sub>g</sub>-101  
Professional series: CRI 90 | TM-30-15 R<sub>f</sub>-90 | TM-30-15 R<sub>g</sub>-101

how to specify ZELA Fixed

Please confirm model option availability from our website. **Not every combination is compatible.**

e.g. code = **SLDL211F-4030P-TWD15**

Model	Beam	CCT	CRI	Trim Colour	Driver	Market
SLDL214F = Lens	09 = 9°	24 = 2400K	P = 90-94	TW = Textured white	Phase cut	= NZ 1 = Aust 2 = UK 3 = EU
SLDL216F = Honeycomb	15 = 15°	27 = 2700K	A = 95-98	TB = Textured black	D08 = 100mA (4.3W)	
SLDL212F = ULG clear	20 = 20°	30 = 3000K			D09 = 150mA (6.4W)	
SLDL211F = Prismatic	30 = 30°	40 = 4000K			D15 = 180mA (7.7W)	
SLDL213F = Opaque	40 = 40°	SD = Sunset			D10 = 220mA (9.4W)	
	55 = 55°	Dimming			D11 = 260mA (11.1W)	
	90 = 90°	S2 = Tunable White			D04 = 260mA (11.9W)	
					<b>DALI</b>	
					D02 = 180mA (8.3W)	<b>DALI TW</b>
					D03 = 230mA (10.1W)	D41 = 150mA (6.9W)
					D04 = 260mA (11.9W)	D42 = 180mA (8.3W)
						D43 = 230mA (10.1W)
						D44 = 260mA (11.9W)
						<b>Casambi TW</b>
						D50 = 100mA (4.6W)
						D51 = 150mA (6.8W)
						D52 = 180mA (8.2W)
						D53 = 220mA (10W)
						D54 = 260mA (11.8W)