



ZELA look-up table

CCT	Driver Power*	SLDL234T						SLDL236T				SLDL231T				SLDL230T				SLDL233T		
		9° Lens		15° Lens		20° Lens		30° Honeycomb		40° Honeycomb		40° Prismatic		55° Prismatic		40° Clear		55° Clear		90° Opaque		
		CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	CRI	Lm	
2400K	4.3W / 100mA	ICF	-	-	-	-	90	340	90	260	90	240	90	360	90	340	90	360	90	340	90	310
	6.4W / 150mA	ICF	-	-	-	-	90	490	90	370	90	340	90	510	90	490	90	510	90	490	90	440
	7.7W / 180mA	ICF	-	-	-	-	90	570	90	430	90	400	90	600	90	570	90	600	90	570	90	520
	9.4W / 220mA	ICF	-	-	-	-	90	670	90	510	90	470	90	700	90	670	90	700	90	670	90	610
	11.1W / 260mA	ICF	-	-	-	-	90	760	90	570	90	540	90	800	90	760	90	800	90	760	90	690
2700K	4.3W / 100mA	ICF	97	280	90	300	90	360	90	280	90	260	90	380	90	370	380	90	370	400	90	330
	6.4W / 150mA	ICF	97	390	90	440	90	520	90	390	90	370	90	550	90	520	550	90	520	570	90	470
	7.7W / 180mA	ICF	97	460	90	510	90	600	90	460	90	430	90	640	90	610	640	90	610	660	90	550
	9.4W / 220mA	ICF	-	-	90	600	90	710	90	540	90	500	90	750	90	720	750	90	720	780	90	650
	11.1W / 260mA	ICF	-	-	90	680	90	810	90	610	90	570	90	850	90	820	850	90	820	880	90	730
3000K	4.3W / 100mA	ICF	97	290	90	320	90	380	90	290	90	270	90	400	90	380	90	400	90	380	90	340
	6.4W / 150mA	ICF	97	410	90	450	90	540	90	410	90	380	90	570	90	550	90	570	90	550	90	490
	7.7W / 180mA	ICF	97	470	90	530	90	630	90	480	90	450	90	660	90	640	90	660	90	640	90	570
	9.4W / 220mA	ICF	-	-	90	620	90	740	90	560	90	520	90	780	90	750	90	780	90	750	90	670
	11.1W / 260mA	ICF	-	-	90	700	90	880	90	640	90	590	90	880	90	850	90	880	90	850	90	760
4000K	4.3W / 100mA	ICF	97	300	90	330	90	400	90	300	90	280	90	420	90	400	90	420	90	400	90	360
	6.4W / 150mA	ICF	97	430	90	480	90	570	90	430	90	400	90	600	90	570	90	600	90	570	90	520
	7.7W / 180mA	ICF	97	500	90	550	90	660	90	500	90	470	90	700	90	670	90	700	90	670	90	600
	9.4W / 220mA	ICF	-	-	90	650	90	780	90	590	90	550	90	820	90	780	90	820	90	780	90	710
	11.1W / 260mA	ICF	-	-	90	740	90	880	90	670	90	620	90	930	90	890	90	930	90	890	90	800
Sunset Dimming 3000K-1850K	6.4W / 150mA	ICF	-	-	-	-	-	-	90	310	90	280	90	460	90	450	90	460	90	450	-	-
	7.7W / 180mA	ICF	-	-	-	-	-	-	90	360	90	320	90	530	90	520	90	530	90	520	-	-
	9.4W / 220mA	ICF	-	-	-	-	-	-	90	420	90	380	90	600	90	610	90	600	90	610	-	-
	11.1W / 260mA	ICF	-	-	-	-	-	-	90	480	90	430	90	710	90	690	90	710	90	690	-	-
Tunable White 4000K-1800K	4.6W / 100mA	ICF	-	-	-	-	95	270	95	200	95	200	95	270	95	270	95	270	95	270	-	-
	6.9W / 150mA	ICF	-	-	-	-	95	380	95	290	95	280	95	390	95	390	95	390	95	390	-	-
	8.3W / 180mA	ICF	-	-	-	-	95	440	95	340	95	330	95	450	95	460	95	450	95	460	-	-
	10.1W / 230mA	ICF	-	-	-	-	95	520	95	400	95	390	95	530	95	540	95	530	95	540	-	-
	11.9W / 260mA	ICF	-	-	-	-	95	590	95	450	95	440	95	600	95	610	95	600	95	610	-	-

\*Watts quoted are for 20°-90° beam angles. Please check ies files at [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for specific model watts for 9° and 15° beam angles.

Please note: Tunable White lumens are for 3000K at CRI 95 (Art series).

Typically used for general lighting.

Contact Switch Lighting for all other output and driver options.

Please visit [www.switch-lighting.co.nz](http://www.switch-lighting.co.nz) for our Lux calculator.

Colour rendition:

Art series: CRI 97 | TM-30-15 R<sub>f</sub>-95 | TM-30-15 R<sub>g</sub>-101

Professional series: CRI 90 | TM-30-15 R<sub>f</sub>-90 | TM-30-15 R<sub>g</sub>-101

how to specify ZELA Tilt 2

Please confirm model option availability from our website. **Not every combination is compatible.**

e.g. code = **SLDL230T-5530A-TWD11** OR **SLDL230T-5530A-TWD04**

Model	Beam	CCT	CRI	Trim Colour	Driver	Market	
SLDL234T = Lens SLDL236T = Honeycomb <b>SLDL230T</b> = Clear glass SLDL231T = Prismatic SLDL233T = Opaque	09 = 9° 15 = 15° 20 = 20° 30 = 30° 40 = 40° <b>55</b> = 55° 90 = 90°	24 = 2400K 27 = 2700K <b>30</b> = 3000K 40 = 4000K SD = Sunset Dimming S2 = Tunable White	P = 90-94 <b>A</b> = 95-98	<b>TW</b> = Textured white <b>TB</b> = Textured black	<b>Phase cut</b> D08 = 100mA (4.3W) D09 = 150mA (6.4W) D15 = 180mA (7.7W) D10 = 220mA (9.4W) <b>D11</b> = 260mA (11.1W) <b>DALI</b> D02 = 180mA (8.3W) D03 = 230mA (10.1W) <b>D04</b> = 260mA (11.9W)	<b>DALI TW</b> D41 = 150mA (6.9W) D42 = 180mA (8.3W) D43 = 230mA (10.1W) D44 = 260mA (11.9W) <b>Casambi TW</b> D50 = 100mA (4.6W) D51 = 150mA (6.8W) D52 = 180mA (8.2W) D53 = 220mA (10W) D54 = 260mA (11.8W)	<b>I</b> = NZ 1 = Aust 2 = UK 3 = EU